

# Honeywell Genetron® Refrigerants



**Refrigerants with the future in mind**

## **Genetron Refrigerants**

### **A world leader in the invention, manufacture and supply of environmentally safer refrigerants**

#### **Honeywell's Genetron Refrigerants**

In these changing times, it's important to have a knowledgeable refrigerant partner that can help your business make the transition to environmentally safer hydrofluorocarbon products. Honeywell strives to be that full-service supplier by providing products and support programs that meet the changing needs of air conditioning and refrigeration professionals. The broad product line we offer features Genetron brand solutions for virtually every application in air conditioning and refrigeration.

#### **Technical Support**

Honeywell's Genetron refrigerants are brought to you by some of the most knowledgeable people in the industry. These engineers and specialists work with the leading equipment and compressor manufacturers to guarantee that Genetron refrigerants will meet your needs today and in the future. Honeywell also serves as a valuable information resource to the industry by offering a full complement of informational materials, ranging from technical bulletins and retrofit guidelines to in-field presentations made by our sales and technical professionals.

#### **Air Conditioning**

A variety of environmentally safer alternatives are available from Honeywell for the air conditioning industry. For the unitary-air-conditioning market, we offer non-ozone-depleting replacements for R-22, including Genetron 407C and Genetron AZ-20® (R-410A). R-410A is an azeotrope-like mixture of HFC-32 and HFC-125 that was invented and patented by Honeywell. Our AZ-20 brand of R-410A has been selected by equipment manufacturers as the refrigerant of choice for providing non-ozone-depleting air conditioning and heat pump options to homeowners.

Our alternative refrigerants for centrifugal chillers include Genetron 123, 245fa, and 134a. Genetron 245fa is a non-ozone depleting fluid developed by Honeywell for use in centrifugal chillers. Genetron AZ-50® (R-507) and AZ-20 are available for positive displacement chiller applications.

As a major supplier to the world's leading automobile and truck manufacturers, we offer a non-ozone-depleting refrigerant, Genetron 134a, for mobile air conditioning systems. As an aid to automotive mechanics worldwide, we offer Genetron 134aUV — a mixture of Genetron 134a and a refrigerant-soluble dye that fluoresces when viewed under ultraviolet light. This novel solution now makes it easier, cleaner, and less expensive to pinpoint leaks in automotive air conditioning systems.

#### **Refrigeration**

The flagship of Honeywell's R-22 replacements is Genetron® Performax™ LT. Genetron Performax LT is a low toxicity, non-flammable replacement for R-22 suitable for both refrigeration system retrofits and new installations. Genetron Performax LT is a close capacity match to R-22 in both medium- and low-temperature applications. The efficiency of Genetron Performax LT is highest among currently available replacements hence it contributes to low operating costs. Because no TXV changes or adjustments are needed, retrofit costs are low. The global warming potential of Performax LT is lower than comparable products.

Honeywell offers a broad line of R-502 and R-22 replacements for low- and medium-temperature refrigeration systems. A popular alternative is Genetron AZ-50® (R-507), an azeotropic HFC mixture

of R-125 and R-143a invented and patented by Honeywell. R-507 can be used in both low- and medium-temperature refrigeration systems, and in both new equipment and retrofit applications. Sold under our brand name AZ-50, R-507 has been approved by the world's leading refrigeration manufacturers. It is used worldwide in supermarkets and in industrial, food-service, and other applications.

Another alternative to R-502 and R-22 is Genetron 404A, which is used in both low- and medium-temperature systems. Genetron HP80 and Genetron 408A are also excellent interim products for low- and medium-temperature applications.

For medium-temperature systems, we manufacture interim products such as Genetron MP39, Genetron MP66 and Genetron 409A for retrofitting applications. We also offer Genetron 134a as a long-term non-ozone-depleting solution for new and retrofit medium-temperature refrigeration systems.

#### **Retrofitting**

Retrofitting existing refrigeration systems to environmentally safer refrigerants plays a major role in the industry's move away from ozone depleting substances. Honeywell encourages its customers to retrofit systems now to help guarantee their smooth and economical operation over the long term.

Comprehensive information is available to help retrofit refrigeration systems to all of our alternative refrigerants.

#### **Reclamation**

As a responsible chemical producer, Honeywell discourages any unnecessary release of refrigerants to the atmosphere and encourages contractors and end-users to return used refrigerant for reclamation and eventual re-use. Honeywell offers an economical refrigerant reclamation program through our network of wholesalers and distributors.

#### **Technical Expertise**

An integral part of Honeywell's investment in non-ozone-depleting fluorocarbon products is the company's Fluorine Products Technology Center in Buffalo, N.Y. This world-class research facility plays a leading role in our application support programs for customers. Some of the work performed at the center includes materials compatibility, lubricant miscibility and system performance testing.



# Genetron Refrigerants Products Guide

## Selected Physical Data

	123	245fa	124	134a
Substitutes (See Legend Below)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
ASHRAE Number	R-123	R-245fa	R-124	R-134a
Molecular Weight	152.9	134.0	136.5	102.0
Boiling Point @ 1 Atm, * (°F)	82.1	59.3	10.5	-14.9
Freezing Point @ 1 Atm, (°F) [Pure Fluids*]	-160.9	-151.8	-326.5	-153.9
Critical Temperature* (°F)	362.6	309.2	252.1	213.9
Critical Pressure* (psia)	531.1	529.5	525.7	588.8
Saturated Liquid Density @ 86°F,* (lb/ft3)	90.6	82.7	83.5	74.1
Specific Heat of Liquid @ 86°F,* (Btu/lb °F)	0.25	0.32	0.27	0.35
Specific Heat of Vapor @ Constant Pressure* (Cp), @ 86°F and 1 Atm, (Btu/lb °F)	0.17	0.22	0.18	0.21
Flammable range, (Based on ASHRAE Standard 34 with Match Ignition)††	None	None	None	None
ANSI/ASHRAE Standard 34-1992 Safety Group Classification	B1	A1	N.C.†††	A1

### Legend:

- CFC 11 Substitutes
- CFC 12 Substitutes
- R-502 Substitutes
- CFC 13/R-503 Substitutes
- HCFC 22 Substitutes

Refrigerants are listed in highest-to-lowest order according to their boiling point at 1 atmosphere pressure.

**Blend**  
**Pentafluoroethane**  
**Tetrafluoroethane**  
**Isobutane**  
 $(CF_3CHF_2/CF_3CH_2F/(CH_3)_3CH)$   
A non-ozone-depleting replacement for HCFC-22 in low- and medium-temperature commercial refrigeration systems.

**Blend**  
**Difluoromethane**  
**Pentafluoroethane**  
**Tetrafluoroethane**  
 $(CH_2F_2/CF_3CHF_2/CF_3CH_2F)$   
A non-ozone-depleting replacement for HCFC-22 in various air-conditioning applications, as well as in positive displacement refrigeration systems.

**Blend**  
**Pentafluoroethane**  
**Trifluoroethane**  
**Chlorodifluoromethane**  
 $(CF_3CHF_2/CF_3CH_3/CHClF_2)$   
An interim replacement for retrofitting low- and medium-temperature commercial refrigeration systems.

**Blend**  
**Difluoromethane**  
**Pentafluoroethane**  
**Tetrafluoroethane**  
 $(CH_2F_2/CF_3CHF_2/CF_3CH_2F)$   
Well-matched performer as a non-ozone depleting replacement for R-22 in low- and medium-temperature commercial refrigeration systems.

## Selected Physical Data

	422D	407C	408A	Performax™ LT
Substitutes (See Legend Above)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
ASHRAE Number	R-422D	R-407C	R-408A	R-407F
Molecular Weight	109.9	86.2	87.7	82.1
Boiling Point @ 1 Atm, (°F)	-45.8↖	-46.5↖	-48.3↖	-50.9
Freezing Point @ 1 Atm, (°F)	—	-256.0	—	—
Critical Temperature* (°F)	175.2	186.9	181.7	180.8
Critical Pressure* (psia)	566.4	671.4	622.9	689.6
Saturated Liquid Density @ 86°F, (lb/ft3)	69.9	69.6	64.8	68.3
Specific Heat of Liquid @ 86°F (Btu/lb• °F)	0.35	0.38	0.35	0.39
Specific Heat of Vapor @ Constant Pressure* (Cp), @ 86°F and 1 Atm, (Btu/lb• °F)	0.20	0.20	0.19	0.2
Flammable range, (Based on ASHRAE Standard 34 with Match Ignition)††	None	None	None	None
ANSI/ASHRAE Standard 34-1992 Safety Group Classification	A1	A1	A1	A1

\* NIST REFPROP 8, unless noted otherwise

↖ Bubble point temperature.

↑ Upper and lower vapor flammability (Vol.%).

†† ASTM E681-85 match ignition ambient conditions.

††† N.C. Not Classified.

Ω @ -30°F.

Contains HFC-125/  
HFC-134a/HC-600a

Contains HFC-32/  
HFC-125/HFC-134a

Contains HFC-125/  
HFC-143a/HCFC-22

Contains HFC-32/  
HFC-125/HFC-134a



## Blend

Chlorodifluoromethane  
Difluoroethane  
Chlorotetrafluoroethane  
 $(\text{CHClF}_2/\text{CHF}_2\text{CH}_3/\text{CHClFCF}_3)$   
An interim replacement for  
CFC-12 in medium-temperature  
commercial refrigeration  
systems.

## Blend

Chlorodifluoromethane  
Difluoroethane  
Chlorotetrafluoroethane  
 $(\text{CHClF}_2/\text{CHF}_2\text{CH}_3/\text{CHClFCF}_3)$   
An interim replacement for  
CFC-12 in low-temperature com-  
mercial refrigeration systems.

## Blend

Chlorodifluoromethane  
Chlorotetrafluoroethane  
Chlorodifluoroethane  
 $(\text{CHClF}_2/\text{CHClFCF}_3/\text{CClF}_2\text{CH}_3)$   
An interim replacement for  
CFC-12 in refrigeration systems.

## HCFC

Chlorodifluoromethane  
 $(\text{CHClF}_2)$   
As a refrigerant, operates  
with higher system pressures  
but low compressor displace-  
ment. Popular in residential,  
commercial and industrial  
applications.

# MP39

# MP66

# 409A

# 22

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> <input style="background-color: #800080; border: none; width: 10px; height: 10px; vertical-align: middle;" type="checkbox"/>
R-401A	R-401B	R-409A	R-22
94.4	92.9	97.4	86.5
-27.3°C	-30.2°C	-30.0°C	-41.5
—	—	—	-251.4
225.2	222.0	228.7	205.1
668.3	679.6	681.5	723.7
73.1	76.7	74.6	73.1
0.31	0.30	0.30	0.31
0.18	0.17	0.17	0.16
None	None	None	None
A1	A1	A1	A1

Contains HCFC-22/  
HFC-152a/HCFC-124.

Contains HCFC-22/  
HFC-152a/HCFC-124.

Contains HCFC-22/  
HCFC-124/ HCFC-142b.

## Blend

Pentafluoroethane  
Trifluoroethane  
Tetrafluoroethane  
 $(\text{CF}_3\text{CHF}_2/\text{CF}_3\text{CH}_3/\text{CF}_3\text{CH}_2\text{F})$   
A long-term, non-ozone-  
depleting replacement for  
R-502 in low- and medium-  
temperature commercial  
refrigeration systems.

## Azeotrope

Pentafluoroethane  
Trifluoroethane  
 $(\text{CF}_3\text{CHF}_2/\text{CF}_3\text{CH}_3)$   
A non-ozone depleting  
azeotropic mixture of HFC-125  
and HFC-143a. It has been  
primarily designed to replace  
R-502 in low- and medium-  
temperature commercial  
refrigeration applications such  
as supermarket display cases  
and ice machines.

## Blend

Chlorodifluoromethane  
Pentafluoroethane  
Propane  
 $(\text{CHClF}_2/\text{CF}_3\text{CHF}_2/\text{C}_3\text{H}_8)$   
An interim replacement for  
R-502 used mainly for ice  
machines and soft ice cream  
machines.

## Blend

Chlorodifluoromethane  
Pentafluoroethane  
Propane  
 $(\text{CHClF}_2/\text{CF}_3\text{CHF}_2/\text{C}_3\text{H}_8)$   
An interim replacement for  
retrofitting low- and medium-  
temperature commercial  
refrigeration systems.

## Azeotropic Mixture

Difluoromethane  
Pentafluoroethane  
 $(\text{CH}_2\text{F}_2/\text{CF}_3\text{CHF}_2)$   
Widely accepted to replace  
HCFC-22 in air conditioning and  
refrigeration applications.

## HFC

Trifluoromethane  
 $(\text{CHF}_3)$   
A specialty low temperature  
refrigerant that may be used to  
replace CFC-13 and R-503 in  
the low stage of cascade  
systems.

## Azeotrope

Trifluoromethane  
Hexafluoroethane  
 $(\text{CHF}_3/\text{C}_2\text{F}_6)$   
A non-ozone depleting  
azeotrope of HFC-23 and FC-  
116 used to replace  
CFC-13 and R-503 in the low  
stage of cascade systems.

# 404A

# AZ-50®

# 507

# HP81

# HP80

# AZ-20®

# 410A

# 23

# 508B



R-404A

R-507, R-507A

R-402B

R-402A

R-410A

R-23

R-508B

97.6

98.9

94.7

101.6

72.6

70.0

95.4

-51.2°C

-52.2°C

-52.7

-56.1°C

-60.6

-115.6

-125.7

—

-178.0

—

-153.0

-247.0

-247.2

—

161.7

159.1

181.2

168.5

160.4

79.1

52.2

540.8

537.4

654.9

612.0

711.0

700.8

547.0

63.6

63.8

70.4

70.0

64.5

77.6 Ω

78.8 Ω

0.38

0.38

0.33

0.34

0.42

0.34 Ω

0.31 Ω

0.21

0.21

0.18

0.18

0.20

0.16 Ω

0.16 Ω

None

None

None

None

None

None

None

A1

A1

A1

A1

A1

N.C.†††

A1

Contains HFC-125/  
HFC-143a/HFC-134a.

Contains HCFC-22/  
HFC-125/HC-290

Contains HFC-  
125/HFC-143a.

Contains HCFC-22/  
HFC-125/HC-290.

Contains HFC-32/HFC-125.

Contains HFC-23/FC-116.

# Vapor Pressures

Temp °F	Bubble Dew		Bubble Dew		Bubble Dew		Bubble Dew		Bubble Dew		Bubble Dew		Bubble Dew		Bubble Dew		Bubble Dew		Bubble Dew						
	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)			
-40	22.1 *	14.8 *	8.4 *	13.8 *	6.7 *	12.4 *	6.7 *	14.8 *	0.6	2.4	2.3 *	2.7	4.6 *	3.5	3.1	4.9	0.5	4.9	4.3	5.4	5.6	3.7	7.4	5.7	10.8
-35	20.9 *	12.5 *	5.3 *	11.4 *	3.4 *	9.7 *	3.5 *	12.5 *	2.6	4.6	0.8	5.1	0.9 *	5.8	5.5	7.5	1.9	7.5	6.8	8.1	8.2	6.2	10.3	8.4	14.1
-30	19.4 *	9.8 *	2.0 *	8.7 *	0.1	6.8 *	0.0	9.9 *	4.9	7.1	3.0	7.7	1.6	8.5	8.0	10.4	4.2	10.3	9.6	11.0	11.1	8.9	13.4	11.4	17.8
-25	17.8 *	6.9 *	0.8	5.6 *	2.0	3.5 *	1.9	7.0 *	7.4	9.9	5.4	10.6	3.9	11.3	10.9	13.6	6.8	13.4	12.7	14.1	14.2	11.9	16.8	14.6	21.9
-20	16.0 *	3.7 *	2.9	2.2 *	4.1	0.1	4.0	3.8 *	10.2	12.9	8.1	13.7	6.5	14.5	14.0	17.1	9.7	16.8	16.0	17.6	17.7	15.1	20.5	18.2	26.3
-15	14.0 *	0.1 *	5.1	0.7	6.5	2.0	6.3	0.2 *	13.2	16.2	11.0	17.2	9.3	17.9	17.4	20.9	12.9	20.5	19.7	21.4	21.4	18.7	24.5	22.5	31.2
-10	11.8 *	1.9	7.5	2.8	9.1	4.2	8.8	1.8	16.5	19.8	14.3	20.9	12.3	21.7	21.1	25.1	16.4	24.6	23.6	25.5	25.5	22.6	28.8	26.3	36.5
-5	9.3 *	4.1	10.1	5.0	11.9	6.6	11.6	4.0	20.1	23.7	17.8	25.0	15.7	25.7	25.1	29.6	20.2	28.9	27.9	30.0	29.9	26.8	33.6	30.8	42.2
0	6.6 *	6.5	13.0	7.4	14.9	9.2	14.6	6.3	24.0	27.9	21.7	29.5	19.4	30.1	29.5	34.5	24.4	33.7	32.6	34.8	34.6	31.4	38.7	35.8	48.4
5	3.6 *	9.1	16.1	10.1	18.2	12.1	17.8	8.8	28.3	32.5	25.8	34.3	23.5	34.9	34.2	39.8	28.9	38.8	37.7	40.1	39.8	36.3	44.2	41.2	55.2
10	0.3 *	11.9	19.5	13.0	21.8	15.2	21.3	11.6	32.8	37.5	30.4	39.5	27.9	40.0	39.3	45.6	33.9	44.3	43.1	45.7	45.3	41.6	50.2	46.9	62.4
15	1.6	15.0	23.1	16.2	25.7	18.6	25.1	14.7	37.8	42.8	35.3	45.2	32.7	45.5	44.8	51.8	39.3	50.2	49.0	51.8	51.3	47.4	56.5	53.2	70.3
20	3.6	18.4	27.1	19.6	29.9	22.3	29.2	18.0	43.1	48.5	40.7	51.2	37.9	51.5	50.7	58.5	45.1	56.6	55.3	58.3	57.7	53.6	63.4	59.8	78.7
25	5.7	22.1	31.4	23.4	34.4	26.3	33.6	21.6	48.8	54.7	46.4	57.7	43.5	57.8	57.0	65.6	51.4	63.4	62.1	65.3	64.5	60.2	70.7	67.0	87.7
30	8.0	26.1	36.0	27.4	39.3	30.6	38.4	25.5	55.0	61.3	52.6	64.7	49.6	64.6	63.7	73.3	58.2	70.7	69.3	72.7	71.8	67.3	78.6	74.7	97.4
35	10.5	30.4	40.9	31.8	44.5	35.2	43.4	29.7	61.5	68.4	59.3	72.2	56.1	71.9	71.0	81.5	65.5	78.6	77.1	80.7	79.7	75.0	86.9	82.9	107.7
40	13.2	35.0	46.2	36.5	50.1	40.2	48.9	34.2	68.6	75.9	66.4	80.2	63.2	79.7	78.7	90.3	73.4	86.9	85.4	89.3	88.0	83.1	95.8	91.6	118.8
45	16.1	40.1	51.8	41.6	56.0	45.6	54.7	39.1	76.1	84.0	74.0	88.8	70.7	88.0	87.0	99.7	81.8	95.8	94.2	98.3	96.9	91.7	105.3	100.9	130.6
50	19.3	45.4	57.9	47.0	62.4	51.4	60.9	44.3	84.1	92.6	82.2	97.9	78.8	96.8	95.7	109.7	90.8	105.3	103.6	108.0	106.3	101.0	115.4	110.9	143.2
55	22.7	51.2	64.3	52.8	69.2	57.5	67.5	49.9	92.6	101.7	90.9	107.6	87.5	106.2	105.1	120.4	100.5	115.3	113.6	118.3	116.3	110.8	126.1	121.4	156.5
60	26.3	57.4	71.2	59.0	76.5	64.1	74.5	55.9	101.6	111.4	100.2	117.9	96.8	116.1	115.0	131.7	110.8	126.0	124.2	129.2	127.0	121.2	137.4	132.6	170.7
65	30.2	64.0	78.5	65.7	84.2	71.2	81.9	62.3	111.2	121.7	110.1	128.9	106.7	126.7	125.5	143.7	121.8	137.3	135.5	140.8	138.2	132.2	149.4	144.4	185.8
70	34.4	71.1	86.3	72.8	92.3	78.7	89.8	69.2	121.4	132.6	120.7	140.5	117.3	137.8	136.6	156.4	133.5	149.3	147.4	153.0	150.1	143.9	162.1	157.0	201.8
75	38.9	78.7	94.5	80.3	101.0	86.7	98.2	76.4	132.2	144.1	131.8	152.8	128.6	149.6	148.3	169.9	146.0	162.0	160.1	165.9	162.7	156.3	175.5	170.2	218.7
80	43.7	86.7	103.2	88.4	110.1	95.2	107.0	84.2	143.6	156.3	143.7	165.8	140.5	162.1	160.8	184.1	159.2	175.4	173.4	179.6	176.0	169.4	189.7	184.2	236.5
85	48.8	95.2	112.4	96.9	119.8	104.2	116.4	92.5	155.7	169.2	156.2	179.6	153.2	175.3	173.9	199.1	173.3	189.5	187.5	194.1	190.0	183.2	204.6	199.0	255.4
90	54.3	104.3	122.2	106.0	130.1	113.8	126.2	101.2	168.4	182.8	169.5	194.1	166.7	189.2	187.7	215.0	188.2	204.5	202.4	209.3	204.7	197.8	220.3	214.6	275.4
95	60.1	113.9	132.5	115.6	140.9	123.9	136.6	110.5	181.8	197.1	183.6	209.4	181.0	203.8	202.3	231.7	203.9	220.2	218.1	225.4	220.2	213.1	236.8	231.0	296.4
100	66.2	124.2	143.3	125.7	152.3	134.7	147.6	120.3	195.9	212.2	198.4	225.5	196.1	219.2	217.6	249.3	220.6	236.8	234.6	242.3	236.5	229.2	254.2	248.3	318.6
105	72.7	135.0	154.8	136.5	164.3	146.0	159.1	130.7	210.8	228.0	214.0	242.4	212.1	235.3	233.8	267.8	238.3	254.2	252.1	260.1	253.7	246.2	272.5	266.5	341.9
110	79.6	146.4	166.8	147.8	176.9	158.0	171.2	141.7	226.4	244.7	230.5	260.3	229.0	252.3	250.7	287.2	256.9	272.5	270.4	278.8	271.7	264.1	291.6	285.6	366.4
115	86.9	158.4	179.4	159.8	190.1	170.6	183.9	153.3	242.8	262.3	247.9	279.0	246.9	270.2	268.6	307.6	279.6	291.8	289.6	298.5	290.5	282.8	311.8	305.7	392.3
120	94.6	171.2	192.7	172.4	204.0	183.9	197.2	165.6	260.0	280.7	266.3	298.6	265.8	288.9	287.3	329.0	297.4	312.1	309.9	319.2	310.3	302.5	332.9	326.7	419.4
125	102.8	184.6	206.6	185.7	218.6	197.9	211.1	178.5	278.0	300.0	285.5	319.2	285.7	308.6	306.9	351.5	319.3	333.3	331.2	340.9	331.0	323.1	355.0	348.9	447.9
130	111.3	198.7	221.2	199.7	233.9	212.1	225.7	192.0	296.9	320.2	305.8	340.7	306.7	329.2	327.4	375.0	342.4	355.7	353.5	363.8	352.7	344.8	378.1	372.1	477.9
135	120.4	213.6	236.5	214.5	250.0	228.1	241.0	206.3	316.7	341.5	327.2	363.3	328.8	350.7	349.0	399.7	366.8	379.1	377.0	387.8	375.4	367.4	402.4	396.4	509.4
140	129.9	229.2	252.5	229.9	266.7	244.3	257.0	221.3	337.4	363.7	349.6	387.0	352.1	373.3	371.5	425.4	392.4	403.7	401.7	413.0	399.2	391.2	427.8	421.9	542.5
145	139.9	245.7	269.3	246.2	284.3	261.4	273.7	237.1	359.0	387.0	373.3	411.7	376.6	397.0	395.2	452.4	419.5	429.6	427.7	439.5	424.0	416.1	454.5	448.7	577.3
150	150.4	262.9	286.8	263.2	302.6	279.3	291.1	253.6	381.7	411.4	398.2	437.5	402.5	421.7	419.9	480.6	448.0	456.8	455.1	467.4	450.0	442.2	482.3	476.9	613.9

## High Boiling Temperature

TEMP °F	123	24

## Worldwide Sales Offices

For more information contact your Honeywell Refrigerants representative

### United States

Honeywell International  
101 Columbia Road  
Morristown, NJ 07962-1053  
Phone: 800-631-8138  
Fax: 973-455-6395

### Latin America/Caribbean

Honeywell Chemicals Mexico  
Constituyentes 900  
Col. Lomas Atlas  
C.P. 950, Mexico DF  
Mexico  
Phone: 52-55-5549-0303  
Fax: 52-55-5544-9803

### Canada

Honeywell Asca. Inc.  
3333 Unity Drive  
Mississauga, Ontario  
L5L 3S6  
Phone: 905-608-6325  
Fax: 905-608-6327

### Asia-Pacific

Honeywell (China) Co., Ltd.  
No 430, Li Bing Road  
Zhang Jiang Hi-Tech Park  
Pudong New Area, Shanghai 201203  
China  
Phone: 86-21-2894-2000  
Fax: 86-21-5855-2719

Honeywell Japan Inc.  
New Pier Takeshiba  
South Tower Building, 20th Floor  
1-16-1 Kaigan, Minato-ku,  
Tokyo 050022, Japan  
Phone: 81-3-6730-7000  
Fax: 81-3-6730-7221

### Honeywell Chemicals, Korea

6F Janghakjaedan, B/D 44-1  
Bangpo-Dong, Seocho-Ku  
Seoul 137040, Korea  
Phone: 8-22-595-0204  
Fax: 8-22-595-4964

Honeywell Specialty Chemicals  
(Singapore) Pte. Ltd.  
17 Changi Business Park Central 1  
Honeywell Building  
Singapore 486073  
Phone: 65-6355-2828  
Fax: 65-6783-2947

Honeywell Polymers (Australia) Pty.  
Limited  
Gr. Lvl. 71 Queens Road  
Melbourne. 3002  
Australia  
Phone: 61-3-9529-1411  
Fax: 61-3-9510-9837

**Northern, Central, and Eastern Europe, Middle East and Africa**  
Honeywell Belgium NV  
Haasrode Research Park  
Grauwmeer 1  
3001 Heverlee  
Belgium  
Phone: 32-16-391-209 and 391 216  
Fax: 32-16-391-235

**Southern Europe, Turkey and Israel**  
Honeywell Fluorine Products Italia Srl  
V. Le Milanofiori El  
20090 Assago - MI - Italia  
Phone: 39-02-892589600  
Fax: 39-02-57500815

### Customer Service

To place an order from anywhere in the Continental United States, Hawaii and the Caribbean:

Phone: 800-522-8001  
Fax: 800-458-9073

Canada:  
Phone: 800-553-9749  
Fax: 800-553-9750

Northern and Central Europe  
Phone: +32-16-391-209  
Phone: +32-16-391-216  
Fax: +32-16-391-235

Southern Europe, Middle East and Africa  
Phone: +39-02-9379-6777  
ext. 24 / 25 and 26  
Fax: +39-02-9379-6761

Outside these areas:  
Phone: 1-973-455-6300  
Fax: 1-973-455-2763



RESPONSIBLE CARE®

OUR COMMITMENT TO SUSTAINABILITY

### Disclaimer

All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required.

Genetron®, AZ-20® and AZ-50® are registered trademarks of Honeywell International Inc.  
Performax is a trademark of Honeywell International, Inc.

**Honeywell**